

Persona C15 and C25 Card Printers



Solidly constructed and loaded with high-performance features, the Persona® C15 (single-sided printing) and the Persona C25 (dual-sided printing) have just what you are looking for in a mid-range card printer.

These innovative printers are loaded with standard features including:

- High-resolution, edge-to-edge printing for unlimited design possibilities
- Ability to print on a variety of card thicknesses and sizes – from standard ID cards up to CR-90-sized badges on the C15
- 100-card input capacity for longer, uninterrupted batch printing
- LCD display to indicate printer status and diagnostics
- Built-in RAM so your system can process and print cards simultaneously

And for even greater flexibility and security, the Persona C15 and C25 also offer optional magnetic stripe encoding or a smart card contact station so cards can be used for access control, time and attendance, vending and more.

Compare. You'll see that feature for feature, nobody beats the value of Persona!

FAST

AND

RELIABLE

Persona C15/C25

CARD PRINTER SPECIFICATIONS

Print Method:	Dye-Sublimation/Resin Thermal Transfer
Resolution:	300 dpi (11.8 dots/mm)
Colors:	Up to 16.7 million
Print Speed:	C25: Approximately 6 seconds (K)* C15: Approximately 8 seconds (K)* C25: Approximately 30 seconds (YMCKO)* C15: Approximately 35 seconds (YMCKO)* <i>*Indicates the ribbon type and the number of ribbon panels being printed where Y=Yellow, M=Magenta, C=Cyan, K=Resin Black, B=Dye-Sub Black and O=Overlay</i>
Accepted Standard Card Sizes:	C25/C15: CR-80 (3.375" x 2.125" / 85.6mm x 54mm) C15: CR-90 (3.63" x 2.37" / 92mm x 60mm)
Maximum Print Area:	3.37" L x 2.14" W / 85.5mm x 54.5mm (edge-to-edge printing is available on CR-80 cards only)
Maximum Accepted Card Width Range:	C25: CR-80 only C15: 2.1" to 2.63" / 53mm to 67mm
Maximum Accepted Card Length Range:	C25: CR-80 only C15: 3.25" to 3.625" / 82mm to 92mm
Accepted Card Thickness:	C25: .010" to .030" / .254mm to .75mm C15: .010" to .060" / .254mm to 1.5mm
Card Types:	PVC or polyester cards with polished PVC finish; monochrome resin ribbon required for straight polyester cards
Card Capacity:	100 PVC cards (.030"), 300 PVC cards (.010"); auto or manual feed
Display:	LCD display shows printer status and diagnostic error prompts
Software Drivers:	Windows® 3.1x and Windows 95/98, Windows NT and Macintosh® (C15 only)
Interface:	Standard 8-bit Centronics-type parallel (ECP compatible) or Macintosh serial (C15 only); network compatible
Operating Temperature:	65° to 80° F / 18° to 27° C
Humidity:	20-80% non-condensing
Dimensions:	C25: 9.05"H x 17.43"W x 10.94"D 229mmH x 442mmW x 278mmD C15: 8.4"H x 13.6"W x 12.7"D 213mmH x 345mmW x 323mmD
Weight:	C25: 26 lbs. / 11.8 kg C15: 16.3 lbs. / 7.4kg
Agency Listings:	Safety: UL 1950, CSA C2.2 and TÜV-GS (IEC-950) Emissions: FCC Class B, CRC c1374, Class B and TÜV-EMC (IEC-801 -2, -3, -4; CISPR 22, Class B), CE
Supply Voltage:	100-240 VAC
Supply Frequency:	50 Hz/60 Hz
Warranty:	Printer – One year Printhead – One year unlimited-pass usage-allowance with UltraCard cards
Options:	<ul style="list-style-type: none"> •ISO Magnetic Stripe Encoding Module, dual high- and low-coercivity, Tracks 1, 2, and 3 •Smart Card Encoding Contact Station •USB Interface Cable (Windows 98/2000 only) •Ethernet Interface Adapter (Windows only; used for stand-alone networking of printers.)



PERSONA®

6533 Flying Cloud Drive • Eden Prairie, MN 55344 USA
952-941-9470 • 800-459-5636 • Fax: 952-941-7836
SL1165-REV0010

This data sheet is for informational purposes only. FARGO Electronics makes no warranties, expressed or implied, in this summary. Company and product names and data used in sample output are fictitious. Specifications are subject to change without notice. FARGO and Persona are registered trademarks of FARGO Electronics, Incorporated. All other trademarks and registered trademarks are property of their respective companies. This is not an offer of sale.

© 2000, FARGO Electronics, Incorporated. All rights reserved.